

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 10/11/2017

Supersedes Date: 05/31/2013

Version: 2.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

1.2. Intended Use of the Product

Use of the Substance/Mixture: Primer, Additive, Sealer: Cementitious & Gypsum Cements

1.3. Name, Address, and Telephone of the Responsible Party

Company

F.H. LEINWEBER CO., INC.

9812 S. Cicero Avenue

Oak Lawn, IL 60453

T 708-424-7000

www.leinwebercompany.com

Manufacturer

F. H. LEINWEBER CO., INC.

346 W. 107th

Chicago, IL 60628

T 773-568-7722

1.4. Emergency Telephone Number

Emergency Number : 708-424-7000

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Not classified

2.2. Label Elements

GHS-US Labeling

No labeling applicable

2.3. Other Hazards

Exposure to dust generated from dried product may aggravate pre-existing eye, skin, or respiratory conditions. Contains substances that are combustible dusts. If dried and allowed to accumulate, may form combustible dust concentrations in air that could ignite and cause an explosion. Take appropriate precautions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Water	(CAS-No.) 7732-18-5	84.565422 - 95.563896	Not classified
1-Propanesulfonic acid, 2-methyl-2-[(1-oxo-2-propenyl)amino]-, monosodium salt, polymer with 1,3-butadiene and ethenylbenzene	(CAS-No.) 403824-26-0	8.90757 - 11.87676	Comb. Dust
Siloxanes and Silicones, di-Me	(CAS-No.) 63148-62-9	0.1 - 0.3	Not classified
Butanedioic acid, sulfo-, 1,4-bis(1,3-dimethylbutyl) ester, sodium salt	(CAS-No.) 2373-38-8	0.09996 - 0.13328	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318
Polyoxyethylene sorbitan tristearate	(CAS-No.) 9005-71-4	0.01 - 0.05	Not classified
Glycerides, C14-18 mono- and di-	(CAS-No.) 67701-33-1	0 - 0.05	Not classified
Phenol, 4,4',4''-(1-methyl-1-propanyl-3-ylidene)tris[2-(1,1-dimethylethyl)-5-methyl-	(CAS-No.) 1843-03-4	0.03465 - 0.0462	Skin Sens. 1B, H317

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates, petroleum, solvent-dewaxed heavy paraffinic	(CAS-No.) 64742-65-0	0.0168 - 0.0252	Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 1B, H350 Repr. 2, H361 STOT RE 1, H372 Asp. Tox. 1, H304
Dimethyl silicone polymer with silica	(CAS-No.) 67762-90-7	<= 0.018	Not classified
Methylcellulose	(CAS-No.) 9004-67-5	<= 0.014	Comb. Dust
Trisodium EDTA	(CAS-No.) 150-38-9	0.00399 - 0.00532	Eye Irrit. 2, H319 Aquatic Chronic 3, H412 Comb. Dust
Sodium hydroxide	(CAS-No.) 1310-73-2	0.003528 - 0.004704	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Polyethylene glycol	(CAS-No.) 25322-68-3	0.00168 - 0.00224	STOT SE 3, H335
Silica, amorphous	(CAS-No.) 7631-86-9	0.000315 - 0.0014	Not classified
Sulfuric acid	(CAS-No.) 7664-93-9	< 0.001	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
3(2H)-Isothiazolone, 2-methyl-	(CAS-No.) 2682-20-4	0.000672 - 0.000896	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT SE 3, H335 Aquatic Acute 1, H400

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media suitable for surrounding type of fire. Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive. As supplied, this product is a liquid. However, when cured and dried this product may produce combustible dust when cut, sanded, ground, or otherwise processed. Use caution when working with combustible dusts. Use appropriate engineering controls to keep generation of airborne dust to a minimum.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Acrid smoke and irritating fumes.

Other Information: Do not allow run-off from fire fighting to enter drains or water sources.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Avoid heating, thermal decomposition may generate various hydrocarbons and acrid irritating vapors.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep from freezing, material may develop bacteria odor on long term storage.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Metal salts.

Storage Temperature: 4.4 - 43.3 °C (40°F-110°F)

7.3. Specific End Use(s)

Primer, Additive, Sealer: Cementitious & Gypsum Cements

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Polyethylene glycol (25322-68-3)		
USA AIHA	WEEL TWA (mg/m ³)	10 mg/m ³ (MW>200-aerosol)
Sodium hydroxide (1310-73-2)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
Silica, amorphous (7631-86-9)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	6 mg/m ³
USA IDLH	US IDLH (mg/m ³)	3000 mg/m ³
Sulfuric acid (7664-93-9)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.2 mg/m ³ (thoracic particulate matter)
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen contained in strong inorganic acid mists
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1 mg/m ³
USA IDLH	US IDLH (mg/m ³)	15 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls

: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear chemically resistant protective gloves.

Eye and Face Protection

: Chemical goggles or safety glasses.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: White, milky
Odor	: Slight.
Odor Threshold	: No data available
pH	: 4 - 10
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: 100 °C (212 °F)
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: Not applicable
Vapor Pressure	: 17.5 mm Hg @68°F (20°C)
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: (0.98-1.04)
Solubility	: Water: Product is dilutable
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Metal salts.
- 10.6. Hazardous Decomposition Products:** Acrid smoke and irritating fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

Trisodium EDTA (150-38-9)	
LD50 Oral Rat	2150 mg/kg
Butanedioic acid, sulfo-, 1,4-bis(1,3-dimethylbutyl) ester, sodium salt (2373-38-8)	
LD50 Oral Rat	1750 mg/kg
LD50 Dermal Rabbit	4000 mg/kg
Polyethylene glycol (25322-68-3)	
LD50 Oral Rat	22 g/kg
LD50 Dermal Rabbit	> 20 ml/kg
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)	
LD50 Oral Rat	> 15000 mg/kg
LD50 Dermal Rabbit	> 5000 mg/kg
LC50 Inhalation Rat	> 2400 mg/m ³ (Exposure time: 4 h)
LC50 Inhalation Rat	4.71 mg/l/4h (reported as > 4.7 mg/l/4h)
Silica, amorphous (7631-86-9)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 2.2 mg/l (Exposure time: 1 h)
Sulfuric acid (7664-93-9)	
LD50 Oral Rat	2140 mg/kg
Siloxanes and Silicones, di-Me (63148-62-9)	
LD50 Oral Rat	> 24 g/kg

Skin Corrosion/Irritation: Not classified

pH: 4 - 10

Serious Eye Damage/Irritation: Not classified

pH: 4 - 10

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Silica, amorphous (7631-86-9)	
IARC group	3
Sulfuric acid (7664-93-9)	
IARC group	1
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

Sodium hydroxide (1310-73-2)	
LC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	40 mg/l
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Silica, amorphous (7631-86-9)	
LC50 Fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
Sulfuric acid (7664-93-9)	
LC50 Fish 1	500 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
LC50 Fish 2	42 mg/l (Exposure time: 96 h - Species: Gambusia affinis [static])
Glycerides, C14-18 mono- and di- (67701-33-1)	
LC50 Fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)

12.2. Persistence and Degradability

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid	
Persistence and Degradability	Not established.
Siloxanes and Silicones, di-Me (63148-62-9)	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid	
Bioaccumulative Potential	Not established.
Silica, amorphous (7631-86-9)	
BCF Fish 1	(no bioaccumulation expected)
Sulfuric acid (7664-93-9)	
BCF Fish 1	(no bioaccumulation)
Siloxanes and Silicones, di-Me (63148-62-9)	
Bioaccumulative Potential	Not established.

12.4. Mobility in Soil

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid	
Ecology - Soil	Movement in the environment is expected to be limited by the formation of insoluble polymers.

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Trisodium EDTA (150-38-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Phenol, 4,4',4''-(1-methyl-1-propanyl-3-ylidene)tris[2-(1,1-dimethylethyl)-5-methyl- (1843-03-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
3(2H)-Isothiazolone, 2-methyl- (2682-20-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	P - P - indicates a commenced PMN substance. SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule.
Butanedioic acid, sulfo-, 1,4-bis(1,3-dimethylbutyl) ester, sodium salt (2373-38-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Polyethylene glycol (25322-68-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	1000 lb
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Silica, amorphous (7631-86-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Dimethyl silicone polymer with silica (67762-90-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
Methylcellulose (9004-67-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
Polyoxyethylene sorbitan tristearate (9005-71-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
Sulfuric acid (7664-93-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb
SARA Section 313 - Emission Reporting	1 % (acid aerosols including mists, vapors, gas, fog, and other airborne

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	forms of any particle size)
Glycerides, C14-18 mono- and di- (67701-33-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Siloxanes and Silicones, di-Me (63148-62-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).

15.2. US State Regulations

Sulfuric acid (7664-93-9)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Sodium hydroxide (1310-73-2)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Silica, amorphous (7631-86-9)	
U.S. - Massachusetts - Right To Know List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Sulfuric acid (7664-93-9)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision	: 10/11/2017
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 3	Flammable liquids Category 3
Met. Corr. 1	Corrosive to metals Category 1
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2

Leinweber's Liquid Latex, Vinyl-Crete Liquid, Elastex Liquid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin Sens. 1A	Skin sensitization, category 1A
Skin Sens. 1B	Skin sensitization, category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapour
H290	May be corrosive to metals
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)